NSN 5950-01-122-1430

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-122-1430

| Reliability Indicator: | | | | | |
|---|--|--|--|--|--|
| Not established | | | | | |
| Overall Length: | | | | | |
| 4.000 inches | | | | | |
| Frequency Rating: | | | | | |
| 47.0 hertz single component and 63.0 hertz single component | | | | | |
| Input-output Phase Relationship: | | | | | |
| Single phase to single phase single component | | | | | |
| Winding Shielding Method: | | | | | |
| Internally shielded single component | | | | | |
| Body Length: | | | | | |
| 3.250 inches | | | | | |
| Body Width: | | | | | |
| 2.500 inches | | | | | |
| Body Height: | | | | | |
| 2.262 inches | | | | | |
| Maximum Operating Temp: | | | | | |
| 130.0 degrees celsius | | | | | |
| Distance Between Mounting Facility Centers: | | | | | |
| 3.560 inches single mounting facility single center group | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Mounting Facility Quantity: | | | | | |
| 2 single group | | | | | |
| Mounting Method: | | | | | |
| Threaded hole single group | | | | | |
| Winding Function And Quantity: | | | | | |
| 1 primary single component and 2 secondary single component | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 32 single group | | | | | |
| Thread Size: | | | | | |
| 0.138 inches single group | | | | | |
| Winding Operating Current: | | | | | |
| 3.0 amperes ac single component 3rd secondary | | | | | |
| Winding Operating Voltage: | | | | | |
| 115.00 ac volts single component single primary | | | | | |
| Thread Series Designator: | | | | | |
| Unc single group | | | | | |
| Terminal Type And Quantity: | | | | | |
| 6 wire lead | | | | | |
| Shelf Life: | | | | | |
| N/a | | | | | |

NSN 5950-01-122-1430

Power Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0