

View Online at <https://aerobasegroup.com/nsn/5950-01-123-6529>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.530 inches

Body Width:

2.310 inches

Body Height:

3.060 inches

Maximum Operating Temp:

50.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Cubic Measure (non-core):

17.8 cubic inches

Winding Operating Current:

750.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

40.00 ac pounds per hour wet single component 2nd secondary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0