NSN 5950-01-123-9516

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-123-9516

| View Online at https://aerobasegroup.com/nsn/5950-01-123-9516 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.970 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.920 inches single mounting facility single center group |
| Overall Height: |
| 2.474 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.300 inches |
| Body Height: |
| 2.250 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary, fixed autotransformer type single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Current: |
| 209.0 milliamperes ac single component single primary input |
| Winding Operating Voltage: |
| 10.00 ac volts single component single primary output |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 3 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |

No

Demilitarization:

NSN 5950-01-123-9516

Power Autotransformer Transformer - Page 2 of 2



Fiig:

A058b0