

View Online at <https://aerobasegroup.com/nsn/5950-01-126-2891>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.440 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.810 inches single mounting facility single center group

Mounting Hole Diameter:

0.196 inches single group

Impedance Rating In Ohms:

48.0 single component all primary

Frequency Rating:

400.0 hertz single component

Pulse Repetition Rate:

2.0 kilohertz single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.325 inches

Body Width:

3.120 inches

Body Height:

4.120 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

1.6 amperes ac single component 2nd secondary

Dc Resistance Rating In Ohms:

1100.000 single component all primary

Terminal Type And Quantity:

6 solder stud and 2 standoff, threaded stud and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0