NSN 5950-01-126-4363

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-126-4363

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 1.250 inches and 1.320 inches

Body Width:

Between 1.250 inches and 1.320 inches

Body Height:

Between 1.620 inches and 1.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-01-126-4363

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0