NSN 5950-01-126-4832

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-126-4832

| View Online at https://aerobasegroup.com/nsn/5950-01-126-4832 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.130 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.060 inches single group |
| Frequency Rating: |
| 45.0 hertz single component and 5.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 180.0 volt-ampere single component |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 3.880 inches |
| Body Height: |
| 3.750 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Bracket single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 10.0 amperes ac single component single primary |
| Winding Operating Voltage: |
| 55.00 ac volts single component single secondary and 130.00 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 5 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0