

View Online at <https://aerobasegroup.com/nsn/5950-01-126-9748>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.145 inches single group and 0.155 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

Between 1.190 inches and 1.210 inches

Body Width:

Between 1.190 inches and 1.210 inches

Body Height:

Between 0.740 inches and 0.760 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

465.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

22.00 ac volts single component 1st secondary

Test Data Document:

10138-16802 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0