

View Online at <https://aerobasegroup.com/nsn/5950-01-126-9748>

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

0.145 inches single group and 0.155 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

Between 1.190 inches and 1.210 inches

**Body Width:**

Between 1.190 inches and 1.210 inches

**Body Height:**

Between 0.740 inches and 0.760 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

1 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Features Provided:**

Color coded lead

**Winding Operating Current:**

465.0 milliamperes ac single component 1st secondary

**Winding Operating Voltage:**

22.00 ac volts single component 1st secondary

**Test Data Document:**

10138-16802 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0