## NSN 5950-01-127-8658

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-127-8658

| Reliability Indicator:   |
|--|
| Not established  |
| Inductance Rating:   |
| 220.00 microhenries single component single winding  |
| Coil Form Type:  |
| Solid single component   |
| Body Length:   |
| 0.160 inches   |
| Body Width:  |
| 0.130 inches   |
| Body Height:   |
| 0.130 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Friction single group  |
| Detino Metherale   |
| Rating Method:   |
| Electrical single component single winding   |
|  |
| Electrical single component single winding   |
| Electrical single component single winding Winding Operating Current:  |
| Electrical single component single winding  Winding Operating Current:  46.0 milliamperes dc single component single winding   |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:   |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding  |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor:  |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding   |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding Shelf Life:   |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding Shelf Life: N/a                                       |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding Shelf Life: N/a                                       |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding Shelf Life: N/a Unit Of Measure:                      |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding Shelf Life: N/a Unit Of Measure: Demilitarization:    |
| Electrical single component single winding Winding Operating Current: 46.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 21.000 single component single winding Quality Factor: 32 single component single winding Shelf Life: N/a Unit Of Measure: Demilitarization: No |