NSN 5950-01-129-1148

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-129-1148

Reliability	/ Indicator:
Not establi	ished
Hazardou	s Locations/environmental Protection:
Vibration r	esistant
Overall Le	ength:
Between 0	0.260 inches and 0.280 inches
Overall W	lidth:
Between 0	0.140 inches and 0.160 inches
Inductanc	e Rating:
390.00 mia	crohenries single component single winding
Coil Form	Туре:
Solid singl	e component
Core Con	struction:
S0lid singl	e component
Body Heig	ght:
Between 0	0.270 inches and 0.300 inches
Maximum	Operating Temp:
125.0 degi	rees celsius
Inclosure	Туре:
Fully enclo	bsed
Mounting	Method:
Terminal s	single group
Rating Me	ethod:
Electrical s	single component single winding
Winding C	Operating Current:
120.0 millia	amperes dc single component single winding
Dc Resist	ance Rating In Ohms:
22.000 sin	gle component single winding
Quality Fa	actor:
55 single	component single winding
Test Data	Document:
81349-mil-	-prf-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; ex	cludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environme	ental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal ⁻	Type And Quantity:
2 wire lead	t de la construcción de
Specificat	tion Data:
96906-ms2	21424 government standard
Shelf Life:	:
N/a	
Unit Of Me	easure:
 Demilitari	zation
No	

NSN 5950-01-129-1148

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

Mil-std (military Standard):

Mil-prf-15305 spec.

