

View Online at <https://aerobasegroup.com/nsn/5950-01-130-7610>

Reliability Indicator:

Not established

Overall Length:

Between 3.672 inches and 3.704 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.172 inches single mounting facility single center group and 2.204 inches single mounting facility single center group

Overall Height:

2.000 inches

Overall Width:

Between 2.609 inches and 2.641 inches

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

30.0 milliamperes dc single component 2nd secondary

Winding Power Rating:

2.3 volts-amperes single component 3rd secondary

Winding Operating Voltage:

9.50 dc volts single component 4th secondary

Special Features:

Two primary windings and five secondary windings

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0