

View Online at <https://aerobasegroup.com/nsn/5950-01-130-9561>

Reliability Indicator:

Not established

Overall Length:

2.220 inches

Overall Height:

2.280 inches

Mounting Slot Width:

0.016 inches single group and 0.019 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

5.76 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.500 inches

Body Width:

1.320 inches

Body Height:

1.750 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.937 inches single mounting facility single center group and 1.875 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

120.0 milliamperes ac single component single secondary

Winding Operating Voltage:

48.00 ac volts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

81349-mil-t-27/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0