

View Online at <https://aerobasegroup.com/nsn/5950-01-131-2375>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.120 inches

Body Width:

3.000 inches

Body Height:

Between 5.630 inches and 5.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

750.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

48.00 dc volts single component 2nd secondary

Special Features:

1 primary winding; 6 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

25 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0