

View Online at <https://aerobasegroup.com/nsn/5950-01-131-8069>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.062 inches single mounting facility single center group

Mounting Hole Diameter:

0.219 inches single group

Frequency Rating:

47.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.060 inches

Body Width:

2.520 inches

Body Height:

2.750 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

700.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

25.75 ac volts single component 2nd secondary

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0