

View Online at <https://aerobasegroup.com/nsn/5950-01-131-9530>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

Between 0.260 inches and 0.280 inches

**Overall Width:**

Between 0.140 inches and 0.160 inches

**Inductance Rating:**

1.00 millihenries single component single winding

**Coil Form Type:**

Solid single component

**Core Construction:**

Solid single component

**Body Height:**

Between 0.270 inches and 0.300 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding

**Winding Operating Current:**

110.0 milliamperes dc single component single winding

**Dc Resistance Rating In Ohms:**

27.000 single component single winding

**Quality Factor:**

50 single component single winding

**Test Data Document:**

81349-mil-prf-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire lead

**Specification Data:**

96906-ms21424 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0

**Mil-std (military Standard):**

Mil-prf-15305 spec.