

View Online at <https://aerobasegroup.com/nsn/5950-01-131-9989>

Reliability Indicator:

Not established

Inductance Rating:

8.20 microhenries single component single winding

Coil Form Type:

Solid single component

Core Construction:

Powdered single component

Body Length:

Between 0.365 inches and 0.385 inches

Body Outside Diameter:

Between 0.146 inches and 0.166 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

Wsd: engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); landing craft air cushion (lcac); spruance class dd (963); los angeles ssn (688); forrestal cv; sturgeon ssn (637); ticonderoga cg (47); nimitz cvn; kidd ddg

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding

Features Provided:

Tinned wire leads

Winding Operating Current:

360.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

0.600 single component single winding

Quality Factor:

50 single component single winding

Criticality Code Justification:

Feat

Special Features:

Porm 5 pct special tolerance; weapon system essential

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0