NSN 5950-01-132-5796

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-132-5796

view Offilite at https://aerobasegroup.com/hist//0000-01-102-0700
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
1.103 inches
Mounting Hole Diameter:
0.147 inches single group
Inductance Type:
Fixed
Inductance Rating:
1.00 millihenries single component single winding
Frequency Rating:
1.0 kilohertz single component
Overall Diameter:
Between 0.984 inches and 1.103 inches
Maximum Operating Temp:
125.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical and winding turns single component single winding
Features Provided:
Tinned wire leads
Winding Conductor Size:
0.02535 inches american wire gage single component single winding
Dc Resistance Rating In Ohms:
0.208 single component single winding
Test Data Document:
93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 turret
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-01-132-5796

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0