

View Online at <https://aerobasegroup.com/nsn/5950-01-132-5797>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

0.820 inches

Turn Quantity:

200-1/2 single component single winding

Mounting Hole Diameter:

0.147 inches single group

Inductance Type:

Fixed

Inductance Rating:

6.40 millihenries single component single winding

Frequency Rating:

1.0 kilohertz single component

Overall Diameter:

Between 0.834 inches and 0.858 inches

Maximum Operating Temp:

125.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Open

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Winding Conductor Size:

0.12600 inches american wire gage single component single winding

Winding Operating Current:

0.37 amperes dc single component single winding

Dc Resistance Rating In Ohms:

2.145 single component single winding

Test Data Document:

93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0