

View Online at <https://aerobasegroup.com/nsn/5950-01-132-8032>

Reliability Indicator:

Not established

Overall Length:

8.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Overall Height:

5.500 inches

Overall Width:

4.500 inches

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to secondary center tap single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

29.0 milliamperes ac single component single secondary

Winding Operating Voltage:

6.60 ac kilovolts single component single secondary and 7.26 ac kilovolts single component single secondary

Special Features:

One common terminal

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

2 wire lead and 3 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0