

View Online at <https://aerobasegroup.com/nsn/5950-01-133-9259>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.850 inches single mounting facility single center group

Mounting Slot Width:

0.190 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.250 inches

Body Width:

2.312 inches

Body Height:

3.812 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

100.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

103.50 ac volts single component single primary and 126.50 ac volts single component single primary

Terminal Type And Quantity:

7 turret and 3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0