

View Online at <https://aerobasegroup.com/nsn/5950-01-134-1344>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.109 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component or 400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.000 inches

Body Width:

4.750 inches

Body Height:

4.500 inches

Installation For Which Designed:

Indoor nonportable

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

7.0 amperes ac single component single primary

Winding Operating Voltage:

50.40 ac volts single component single primary and 66.40 ac volts single component single primary and 115.00 ac volts single component single primary and 130.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

22 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0