

View Online at <https://aerobasegroup.com/nsn/5950-01-135-0736>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

49.0 hertz single component and 61.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component and internal shield grounded to inclosure and core single component

Body Length:

3.750 inches

Body Width:

3.600 inches

Body Height:

3.125 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

250.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

187.00 ac volts single component all primary and 204.00 ac volts single component all primary

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0