NSN 5950-01-136-4055

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-136-4055

| Reliability Indicator: | | | | | |
|--|--|--|--|--|--|
| Not established | | | | | |
| Turn Quantity: | | | | | |
| 40 single component single winding | | | | | |
| Inductance Type: | | | | | |
| Fixed | | | | | |
| Inductance Rating: | | | | | |
| 60.00 microhenries single component single winding | | | | | |
| Body Length: | | | | | |
| 0.600 inches | | | | | |
| Body Width: | | | | | |
| 0.600 inches | | | | | |
| Body Height: | | | | | |
| 0.670 inches | | | | | |
| Maximum Operating Temp: | | | | | |
| 100.0 degrees celsius | | | | | |
| Winding Quantity: | | | | | |
| 1 single component | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Mounting Facility Quantity: | | | | | |
| 1 single group | | | | | |
| Mounting Method: | | | | | |
| Threaded stud single group | | | | | |
| Rating Method: | | | | | |
| Electrical single component single winding and winding turns single component single winding | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 32 single group | | | | | |
| Thread Size: | | | | | |
| 0.138 inches single group | | | | | |
| Winding Conductor Size: | | | | | |
| 0.02010 inches american wire gage single component single winding | | | | | |
| Winding Operating Current: | | | | | |
| 1.5 amperes dc single component single winding | | | | | |
| Dc Resistance Rating In Ohms: | | | | | |
| 0.126 single component single winding | | | | | |
| Thread Series Designator: | | | | | |
| Unc single group | | | | | |
| Terminal Type And Quantity: | | | | | |
| 2 wire lead | | | | | |
| Shelf Life: | | | | | |
| N/a | | | | | |

NSN 5950-01-136-4055

Reactor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0