NSN 5950-01-138-1880

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-138-1880

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 5.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.500 inches single mounting facility single center group **Frequency Rating:** 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Transformer Winding Connection Type:** Delta-delta Winding Shielding Method: Internal shield brought out to terminal single component **Body Length:** 6.000 inches **Body Width:** 4.000 inches **Body Height:** 2.332 inches **Maximum Operating Temp:** 130.0 degrees celsius Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 6 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

11.64 amperes ac single component 1st secondary

Winding Operating Voltage:

24.63 ac volts single component 1st secondary

Special Features:

Dual terminals for each leg of the primary winding and first secondary winding

Thread Series Designator:

Unf single group

NSN 5950-01-138-1880

Power Transformer - Page 2 of 2



Terminal Type And Quantity:

6 turret and 10 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0