

View Online at <https://aerobasegroup.com/nsn/5950-01-138-1881>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.710 inches single mounting facility single center group and 1.730 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.710 inches single mounting facility single center group and 1.730 inches single mounting facility single center group

Frequency Rating:

17.0 kilohertz single component and 35.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 2.110 inches and 2.130 inches

Body Width:

Between 2.110 inches and 2.130 inches

Body Height:

1.060 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

750.0 milliamperes dc single component 1st secondary and 1.5 amperes dc single component 1st secondary

Winding Operating Voltage:

58.00 ac volts single component 1st secondary

Special Features:

One primary winding; eight secondary windings, first, second, third, fourth, fifth, and sixth secondary center tapped

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

25 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0