

View Online at <https://aerobasegroup.com/nsn/5950-01-138-3196>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.687 inches

Body Width:

4.000 inches

Body Height:

4.937 inches

End Application:

Ticonderoga class cg (47)

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

11.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

32.60 ac volts single component single secondary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0