

View Online at <https://aerobasegroup.com/nsn/5950-01-138-9226>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group and 3.562 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

5.000 inches

Body Width:

3.750 inches

Body Height:

4.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

9.5 amperes dc single component 1st secondary

Winding Operating Voltage:

33.20 ac volts single component 2nd secondary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0