

View Online at <https://aerobasegroup.com/nsn/5950-01-139-0490>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.313 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Frequency Rating:

600.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

12.6 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.063 inches

Body Width:

2.625 inches

Body Height:

4.188 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

3 primary single component and 16 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

200.0 milliamperes ac single component 1st primary

Winding Power Rating:

1.26 volts-amperes single component 1st primary

Winding Operating Voltage:

6.30 ac volts single component 1st primary

Special Features:

Three primary windings and sixteen secondary windings

Terminal Type And Quantity:

39 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0