

View Online at <https://aerobasegroup.com/nsn/5950-01-140-1247>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.115 inches single mounting facility single center group and 6.135 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.690 inches single mounting facility single center group and 5.810 inches single mounting facility single center group

**Mounting Slot Width:**

0.250 inches single group

**Frequency Rating:**

47.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internally shielded single component

**Body Length:**

8.000 inches

**Body Width:**

7.500 inches

**Body Height:**

10.100 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Winding Operating Current:**

8.5 amperes dc single component 3rd secondary

**Winding Operating Voltage:**

10.00 ac volts single component 2nd secondary

**Special Features:**

1 primary winding; 6 secondary windings; primary tap split into 2 terminals

**Terminal Type And Quantity:**

25 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0