

View Online at <https://aerobasegroup.com/nsn/5950-01-140-2444>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.937 inches single mounting facility single center group and 2.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.700 inches single mounting facility single center group and 1.800 inches single mounting facility single center group

Mounting Slot Width:

0.171 inches single group and 0.203 inches single group

Frequency Rating:

47.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.550 inches

Body Width:

2.437 inches

Body Height:

3.125 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

800.0 milliamperes ac single component all secondary

Winding Operating Voltage:

80.00 ac volts single component 2nd secondary and 180.00 ac volts single component 2nd secondary

Test Data Document:

92220-t050-913 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0