

View Online at <https://aerobasegroup.com/nsn/5950-01-140-7127>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches single mounting facility single center group

Mounting Hole Diameter:

0.144 inches single group

Impedance Rating In Ohms:

125.0 single component all secondary

Frequency Rating:

50.0 hertz single component and 20.0 kilohertz single component

Maximum Transformer Power Rating:

200.0 milliwatts single component

Body Length:

2.250 inches

Body Outside Diameter:

1.625 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

8.0 milliamperes dc single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

81349-mil-t-27/197 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0