NSN 5950-01-140-7482

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-140-7482

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

1.103 inches

Turn Quantity:

100-1/2 single component single winding

Mounting Hole Diameter:

0.147 inches single group

Inductance Rating:

2.53 millihenries single component single winding

Overall Diameter:

Between 0.984 inches and 1.024 inches

Maximum Operating Temp:

125.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Open

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Winding Conductor Size:

0.03125 inches american wire gage single component single winding

Winding Operating Current:

0.6 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.479 single component single winding

Test Data Document:

93322-7109257 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5950-01-140-7482

Reactor - Page 2 of 2

Fiig: A058b0

