

View Online at <https://aerobasegroup.com/nsn/5950-01-141-1168>

**Reliability Indicator:**

Not established

**Overall Length:**

5.700 inches

**Turn Quantity:**

385 single component single winding

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.850 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.375 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.250 inches single group

**Inductance Type:**

Fixed

**Inductance Rating:**

330.00 millihenries single component single winding

**Frequency Rating:**

60.0 hertz single component

**Body Length:**

4.200 inches

**Body Height:**

3.000 inches

**Winding Quantity:**

1 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Bracket single group and unthreaded hole single group

**Rating Method:**

Electrical single component single winding and winding turns single component single winding

**Winding Conductor Size:**

0.03196 inches american wire gage single component single winding

**Dc Resistance Rating In Ohms:**

3.800 single component single winding

**Criticality Code Justification:**

Zzzy

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3203

**Terminal Type And Quantity:**

2 tab, solder lug

**Reference Number Differentiating Characteristics:**

Arefernce number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0