NSN 5950-01-141-1168

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-141-1168
Reliability Indicator:
Not established
Overall Length:
5.700 inches
Turn Quantity:
385 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.850 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.375 inches single mounting facility single center group
Mounting Hole Diameter:
0.250 inches single group
Inductance Type:
Fixed
Inductance Rating:
330.00 millihenries single component single winding
Frequency Rating:
60.0 hertz single component
Body Length:
4.200 inches
Body Height:
3.000 inches
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Bracket single group and unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.03196 inches american wire gage single component single winding
Dc Resistance Rating In Ohms:
3.800 single component single winding
Criticality Code Justification:
Zzzy
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3203
Terminal Type And Quantity:

2 tab, solder lug

NSN 5950-01-141-1168

Reactor - Page 2 of 2



Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0