

View Online at <https://aerobasegroup.com/nsn/5950-01-141-5503>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.181 inches single mounting facility single center group and 2.193 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.869 inches single mounting facility single center group and 1.881 inches single mounting facility single center group

Mounting Slot Width:

0.200 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 2.806 inches and 2.818 inches

Body Width:

Between 2.431 inches and 2.443 inches

Body Height:

Between 2.369 inches and 2.381 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Power Rating:

28.0 volts-amperes single component single secondary

Winding Operating Voltage:

28.00 ac volts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0