

View Online at <https://aerobasegroup.com/nsn/5950-01-141-8335>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded to inclosure single component

Body Length:

3.750 inches

Body Width:

3.375 inches

Body Height:

4.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and threaded hole single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

3.4 amperes dc single component 1st secondary

Winding Operating Voltage:

7.00 dc volts single component 2nd secondary

Special Features:

Secondary voltage and current have been rectified

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 terminal block w/screws and 7 quick disconnect, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0