

View Online at <https://aerobasegroup.com/nsn/5950-01-141-8336>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

6.000 inches

Body Width:

3.125 inches

Body Height:

4.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 amperes dc single component single secondary

Winding Operating Voltage:

131.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

4 wire lead and 6 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0