

View Online at <https://aerobasegroup.com/nsn/5950-01-143-0285>

Reliability Indicator:

Not established

Overall Length:

4.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.310 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Overall Height:

4.250 inches

Overall Width:

3.500 inches

Mounting Slot Width:

0.218 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

3.0 amperes ac single component 1st secondary

Winding Operating Voltage:

42.00 ac volts single component single primary and 80.00 ac volts single component single primary and 120.00 ac volts single component single primary and 145.00 ac volts single component single primary and 192.00 ac volts single component single primary

Test Data Document:

13297-1-109901 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0