## NSN 5950-01-143-1695

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-143-1695

Reliability Indicator:

| Not established                                     |
|---|
| Inductance Type:                                    |
| Fixed   |
| Inductance Rating:                                  |
| 300.00 microhenries single component single winding |
| Frequency Rating:                                   |
| 1.0 kilohertz single component                      |
| Body Length:  |
| 0.450 inches  |
| Body Outside Diameter:                              |
| 0.875 inches  |
| Winding Quantity:                                   |
| 1 single component                                  |
| Inclosure Type:                                     |
| Fully enclosed                                      |
| Mounting Facility Quantity:                         |
| 2 single group                                      |
| Mounting Method:                                    |
| Threaded hole single group                          |
| Rating Method:                                      |
| Electrical single component all winding             |
| Thready Qty Per Inch (tpi):                         |
| 40 single group                                     |
| Thread Size:  |
| 0.112 inches single group                           |
| Winding Operating Current:                          |
| 1.0 amperes dc single component single winding      |
| Dc Resistance Rating In Ohms:                       |
| 90.000 single component single winding              |
| Thread Series Designator:                           |
| Unc single group                                    |
| Terminal Type And Quantity:                         |
| 2 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| Yes - demil/mli                                     |
| Fiig:   |

A058b0