

View Online at <https://aerobasegroup.com/nsn/5950-01-144-1196>

Reliability Indicator:

Not established

Overall Length:

9.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.500 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.500 inches all mounting facilities all center groupings

Overall Height:

8.000 inches

Overall Width:

10.750 inches

Frequency Rating:

60.0 hertz all components

Input-output Phase Relationship:

Single phase to single phase all components

Winding Shielding Method:

Internal shield brought out to terminal all components

Inclosure Type:

Open

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Slot all groupings

Winding Function And Quantity:

2 primary all components and 2 secondary all components

Winding Operating Current:

31.0 amperes ac single component single secondary and 62.0 amperes ac single component single secondary

Winding Power Rating:

7.5 kilovolt-amperes single component single secondary

Winding Operating Voltage:

104.00 ac volts single component single primary and 110.00 ac volts single component single primary and 120.00 ac volts single component single primary and 208.00 ac volts single component single primary and 220.00 ac volts single component single primary and 240.00 ac volts single component single primary

Terminal Type And Quantity:

1 terminal block w/screws and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0