

View Online at <https://aerobasegroup.com/nsn/5950-01-145-8634>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.875 inches single mounting facility single center group

Overall Width:

3.562 inches

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

3.875 inches

Body Height:

3.187 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

100.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

550.00 ac pounds per hour wet single component 4th secondary

Special Features:

Each secondary winding must have seperate electrostatic shield

Cognizant Service:

Usn

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0