

View Online at <https://aerobasegroup.com/nsn/5950-01-145-8634>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.875 inches single mounting facility single center group

**Overall Width:**

3.562 inches

**Frequency Rating:**

47.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internally shielded single component

**Body Length:**

3.875 inches

**Body Height:**

3.187 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Bracket single group and slot single group

**Winding Function And Quantity:**

1 primary single component and 4 secondary single component

**Winding Operating Current:**

100.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

550.00 ac pounds per hour wet single component 4th secondary

**Special Features:**

Each secondary winding must have separate electrostatic shield

**Cognizant Service:**

Usn

**Terminal Type And Quantity:**

13 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0