

View Online at <https://aerobasegroup.com/nsn/5950-01-146-1784>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.310 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.680 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.270 inches

Body Width:

3.650 inches

Body Height:

5.550 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

40.0 amperes ac single component single secondary

Winding Operating Voltage:

6.40 ac volts single component single secondary

Special Features:

Term. 3 and 5, 4 and 6 are internally shorted

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0