

View Online at <https://aerobasegroup.com/nsn/5950-01-147-1660>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group

Overall Width:

1.250 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.160 inches

Body Width:

1.750 inches

Body Height:

1.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

252.0 milliamperes dc single component single primary and 836.0 milliamperes dc single component single primary

Winding Operating Voltage:

186.00 ac volts single component single secondary and 417.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0