# NSN 5950-01-147-1660

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-147-1660

# **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group

## **Overall Width:**

1.250 inches

#### **Frequency Rating:**

400.0 hertz single component

## Input-output Phase Relationship:

Three phase to three phase single component

## **Transformer Winding Connection Type:**

Delta-wye

#### Winding Shielding Method:

Internal shield brought out to terminal single component

#### **Body Length:**

2.160 inches

#### Body Width:

1.750 inches

## **Body Height:**

1.000 inches

#### Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

40 single group

#### **Thread Size:**

0.112 inches single group

## Winding Operating Current:

252.0 milliamperes dc single component single primary and 836.0 milliamperes dc single component single primary

## Winding Operating Voltage:

186.00 ac volts single component single secondary and 417.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

7 tab, solder lug

# NSN 5950-01-147-1660

Power Transformer - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

