

View Online at <https://aerobasegroup.com/nsn/5950-01-148-3082>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.480 inches single mounting facility single center group and 5.520 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.448 inches single mounting facility single center group and 4.500 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

8.000 inches

Body Width:

5.500 inches

Body Height:

6.500 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

7.0 amperes dc single component 2nd secondary

Winding Power Rating:

63.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

9.00 dc volts single component 1st secondary

Special Features:

1 primary winding; 8 secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

5 threaded stud and 20 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0