NSN 5950-01-148-4014

Current Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-148-4014 |
|---|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Moisture resistant |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.680 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.109 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 2.5 volt-ampere single component |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 1.060 inches |
| Body Height: |
| 2.750 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 100.5 amperes ac single component single secondary |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A058b0