## NSN 5950-01-148-4901

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-148-4901

view Offilite at https://acrobasegroup.com/hish/0330-01-140-4301
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.480 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.740 inches single mounting facility single center group
Inductance Type:
Swinging
Inductance Rating:
6.50 millihenries single component 4th winding and 9.00 millihenries single component 4th winding
Frequency Rating:
25.0 kilohertz single component
Body Length:
1.800 inches
Body Width:
1.060 inches
Body Height:
2.000 inches
Maximum Operating Temp:
85.0 degrees celsius
Winding Quantity:
4 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component all winding
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Current:
400.0 milliamperes dc single component 2nd winding and 1.5 amperes dc single component 2nd winding
Dc Resistance Rating In Ohms:
6.000 single component 4th winding
Thread Series Designator:
Unc single group

8 turret

**Terminal Type And Quantity:** 

## NSN 5950-01-148-4901

Reactor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0