

View Online at <https://aerobasegroup.com/nsn/5950-01-148-6853>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.115 inches single mounting facility single center group and 3.135 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group

Overall Height:

3.562 inches

Frequency Rating:

47.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.000 inches

Body Width:

3.375 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

30.0 milliamperes dc single component 4th secondary

Winding Power Rating:

52.5 volts-amperes single component 1st secondary

Winding Operating Voltage:

70.00 dc volts single component 2nd secondary

Special Features:

Two primary windings and five secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0