# NSN 5950-01-148-6853

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-148-6853

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.115 inches single mounting facility single center group and 3.135 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group

## **Overall Height:**

3.562 inches

## **Frequency Rating:**

47.0 hertz single component and 440.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

## Winding Shielding Method:

Internal shield brought out to terminal single component

## Body Length:

4.000 inches

## Body Width:

3.375 inches

### Maximum Operating Temp:

170.0 degrees celsius

### Inclosure Type:

Fully enclosed

#### Mounting Facility Quantity:

4 single group

#### **Mounting Method:**

Threaded hole single group

#### Winding Function And Quantity:

2 primary single component and 5 secondary single component

#### Thread Size:

0.164 inches single group

#### Winding Operating Current:

30.0 milliamperes dc single component 4th secondary

#### Winding Power Rating:

52.5 volts-amperes single component 1st secondary

#### Winding Operating Voltage:

70.00 dc volts single component 2nd secondary

#### **Special Features:**

Two primary windings and five secondary windings

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

21 turret

# NSN 5950-01-148-6853

Power Transformer - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

